
Feature

- 200V,9A
  $R_{DS(ON)}$ <300mΩ @V_{GS}=10V TYP:250 mΩ
- Advanced Planar stripe DMOS Technology
- Lead free product is acquired
- Excellent $R_{DS(ON)}$ and Low Gate Charge



Schematic Diagram

Application

- PWM applications
- Load Switch
- Power management



Marking and pin assignment

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity (PCS)
9N20K	AP9N20K	TO-252	-	-	2500

ABSOLUTE MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	200	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current (T_a =25℃)	I_D	9	A
Avalanche Current(1)	I_{AS}	5	A
Pulsed Drain Currenr (1)	I_{DM}	36	A
Singel Pulsed Avalanche Energy (2)	E_{AS}	115	mJ
Repetitive Avalanche Energy (2)	E_{AR}	69	mJ
Power Dissipation	P_D	74	W
Thermal Resistance from Junction to Case	$R_{\theta JC}$	1.7	℃/W
Junction Temperature	T_J	150	℃
Storage Temperature	T_{STG}	-55~ +150	℃

MOSFET ELECTRICAL CHARACTERISTICS(T_a=25℃ unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Static Characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D =250μA	200	-	-	V
Zero gate voltage drain current	I_{DSS}	V_{DS} =200V, V_{GS} = 0V	-	-	1	μA
Gate-body leakage current	I_{GSS}	V_{GS} =±20V, V_{DS} = 0V	-	-	±100	nA
Gate threshold voltage(3)	$V_{GS(th)}$	V_{DS} =V_{GS}, I_D =250μA	1.0	1.7	2.5	V
Drain-source on-resistance(3)	$R_{DS(on)}$	V_{GS} =10V, I_D =4.5A	-	250	300	mΩ
Dynamic characteristics						
Input Capacitance	C_{iss}	V_{DS} =25V, V_{GS} =0V, f =1.0MHz	-	605	-	pF
Output Capacitance	C_{oss}		-	87	-	
Reverse Transfer Capacitance	C_{rss}		-	37	-	
Switching characteristics						
Turn-on delay time	$t_{d(on)}$	V_{DD}=100V, I_D=9A,V_{GS}=10V, R_G=25Ω	-	35	-	ns
Turn-on rise time	t_r		-	7	-	
Turn-off delay time	$t_{d(off)}$		-	98	-	
Turn-off fall time	t_f		-	32	-	
Total Gate Charge	Qg	VDS=160V, ID=9A, VGS=10V	-	19	-	nC
Gate-Source Charge	Qgs		-	3	-	
Gate-Drain Charge	Qgd		-	8	-	
Source-Drain Diode characteristics						
Diode Forward voltage(3)	V_{DS}	V_{GS} =0V, I_S=4.5A	-	-	1.4	V
Diode Forward current(4)	I_S		-	-	9	A
Body Diode Reverse Recovery Time	trr	T_J=25°， IF=9A,di/dt=100A/us		145		ns
Body Diode Reverse Recovery Charge	Qrr	T_J=25°， IF=9A,di/dt=100A/us		0.82		uc

Notes:

1. Repetitive Rating: pulse width limited by maximum junction temperature
2. EAS Condition:T_J=25℃,V_{DD}=50V,R_G=50Ω,L=10mH
3. Pulse Test: pulse width≤300μs, duty cycle≤2%
4. Surface Mounted on FR4 Board,t≤10 sec

Typical Characteristics T_J = 25ºC, unless otherwise noted

Figure 1. Output Characteristics (T_J= 25ºC)




Figure 2. Body Diode Forward Voltage




Figure 3. Drain Current vs. Temperature




Figure 4. BV_{DSS} Variation vs. Temperature




Figure 5. Transfer Characteristics





Figure 6. On-Resistance vs. Temperature



Typical Characteristics T_J = 25ºC, unless otherwise noted

Figure 7. Capacitance




Figure 8. Gate Charge




Figure 9. Transient Thermal Impedance TO-220F




Figure 10. Transient Thermal Impedance TO-251,TO-252




Figure A：Gate Charge Test Circuit and Waveform




Figure B：Resistive Switching Test Circuit and Waveform






Figure C：Unclamped Inductive Switching Test Circuit and Waveform




TO-252 Package Information



TO-252

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	2.10		2.50	0.083		0.098
A2	0		0.10	0		0.004
B	0.66		0.86	0.026		0.034
B2	5.18		5.48	0.202		0.216
C	0.40		0.60	0.016		0.024
C2	0.44		0.58	0.017		0.023
D	5.90		6.30	0.232		0.248
D1	5.30REF			0.209REF		
E	6.40		6.80	0.252		0.268
E1	4.63			0.182		
G	4.47		4.67	0.176		0.184
H	9.50		10.70	0.374		0.421
L	1.09		1.21	0.043		0.048
L2	1.35		1.65	0.053		0.065
V1		7°			7°	
V2	0°		6°	0°		6°

Reel Specification-TO-252



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
W	15.90	16.00	16.10	0.626	0.630	0.634
E	1.65	1.75	1.85	0.065	0.069	0.073
F	7.40	7.50	7.60	0.291	0.295	0.299
D0	1.40	1.50	1.60	0.055	0.059	0.063
D1	1.40	1.50	1.60	0.055	0.059	0.063
P0	3.90	4.00	4.10	0.154	0.157	0.161
P1	7.90	8.00	8.10	0.311	0.315	0.319
P2	1.90	2.00	2.10	0.075	0.079	0.083
A0	6.85	6.90	7.00	0.270	0.271	0.276
B0	10.45	10.50	10.60	0.411	0.413	0.417
K0	2.68	2.78	2.88	0.105	0.109	0.113
T	0.24		0.27	0.009		0.011
t1	0.10			0.004		
10P0	39.80	40.00	40.20	1.567	1.575	1.583