
Feature


- 100V,80A
  $R_{DS(ON)}$ <8.5 mΩ@V_{GS}=10V TYP:7.2 mΩ
  $R_{DS(ON)}$ < 12.0 mΩ @V_{GS}=4.5V TYP:9.0 mΩ
- Split Gate Trench Technology
- Lead free product is acquired
- Excellent $R_{DS(ON)}$ and Low Gate Charge



Schematic Diagram

Application

- PWM applications
- Load Switch
- Power management



TO-220

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity (PCS)
G085N10	APG085N10	TO-220	-	-	1000

ABSOLUTE MAXIMUM RATINGS (T_J=25℃ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	±25	V
Continuous Drain Current (T_C =25℃)	I_D	80	A
Continuous Drain Current (T_C =100℃)	I_D	50	A
Pulsed Drain Current (1)	I_{DM}	320	A
Singel Pulsed Avalanche Energy (2)	E_{AS}	225	mJ
Power Dissipation	P_D	105	W
Thermal Resistance from Junction to Case	$R_{\theta JC}$	1.2	℃/W
Junction Temperature	T_J	150	℃
Storage Temperature	T_{STG}	-55~ +150	℃

MOSFET ELECTRICAL CHARACTERISTICS(T_J=25℃ unless otherwise noted)


Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Static Characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D =250μA	100	-	-	V
Zero gate voltage drain current	I_{DSS}	V_{DS} =100V, V_{GS} = 0V	-	-	1	μA
Gate-body leakage current	I_{GSS}	V_{GS} =±25V, V_{DS} = 0V	-	-	±100	nA
Gate threshold voltage(3)	$V_{GS(th)}$	V_{DS} =V_{GS}, I_D =250μA	1.5	2.0	3.0	V
Drain-source on-resistance(3)	$R_{DS(on)}$	V_{GS} =10V, I_D =40A	-	7.2	8.5	mΩ
		V_{GS} =4.5V, I_D =40A	-	9.0	12.0	mΩ
Forward Threshold Voltage	g_{fs}	V_{DS} =10V, I_D =40A	-	65	-	S
Gate Resistance	R_g	V_{DS} =V_{GS} =0V, f =1MHz	-	1.3	-	Ω
Dynamic characteristics						
Input Capacitance	C_{iss}	V_{DS} =50V, V_{GS} =0V, f =1MHz	-	3000	-	pF
Output Capacitance	C_{oss}		-	362	-	
Reverse Transfer Capacitance	C_{rss}		-	11	-	
Switching characteristics						
Turn-on delay time	$t_{d(on)}$	V_{DD}=50V, I_D=40A, V_{GS}=10V, R_G=3Ω	-	13	-	ns
Turn-on rise time	t_r		-	35	-	
Turn-off delay time	$t_{d(off)}$		-	20	-	
Turn-off fall time	t_f		-	15	-	
Total Gate Charge	Qg	VDS=50V, ID=40A, VGS=10V	-	30	-	nC
Gate-Source Charge	Qgs		-	10	-	
Gate-Drain Charge	Qgd		-	8	-	
Reverse Recovery Chrage	Qrr	I_F=40A,di/dt=100A/us		90		nC
Reverse Recovery Time	Trr	I_F=40A,di/dt=100A/us		60		ns
Source-Drain Diode characteristics						
Diode Forward voltage(3)	V_{DS}	V_{GS} =0V, I_S=20A	-	-	1.3	V
Diode Forward current(4)	I_S		-	-	80	A

Notes:


1. Repetitive Rating: pulse width limited by maximum junction temperature
2. EAS Condition:T_J=25℃,V_{DD}=50V,R_G=25Ω,L=0.5Mh,IAS=30A
3. Pulse Test: pulse width≤300μs, duty cycle≤2%
4. Surface Mounted on FR4 Board,t≤10 sec

Test Circuit & Waveform


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



Typical Performance Characteristics

Fig.1 Power Dissipation Derating Curve




Fig.2 Avalanche Energy Derating Curve vs. Junction Temperature




Fig.3 Typical Output Characteristics




Fig. 4 Transconductance vs. Drain Current




Fig.5 Typical Transfer Characteristics




Fig. 6 State Resistance vs. Drain Current @-25℃




Fig.7 State Resistance vs. Drain Current @25℃




Fig. 8 State Resistance vs. Drain Current @125℃




Fig.9 Typical Capacitance vs. Drain Source Voltage




Fig.10 Dynamic Input Characteristics




Fig.11 Breakdown Voltage vs. Junction Temperature




Fig. 12 Gate Threshold Voltage vs. Junction Temperature




Fig.13 Safe Operating Area







Fig. 14 Transient Thermal Response Curve



Package Dimensions of TO-220





DIM / SYMBOL	MIN.	NOM.	MAX.
A	4.450	4.550	4.650
A1	1.240	1.340	1.440
A2	2.500	2.600	2.700
b	0.740	0.840	0.940
b1	0.700	0.800	0.900
b2	1.210	1.310	1.410
b3	1.170	1.270	1.370
c	0.440	0.540	0.640
c1	0.400	0.500	0.600
D	9.100	9.200	9.300
D1	15.200	15.400	15.600
D2	12.610	12.810	13.010
E	9.900	10.000	10.100
E1	8.240	8.440	8.640
E2	9.900	10.100	10.300
e	2.540 BSC.		
H1	6.000	6.200	6.400
L	13.140	13.340	13.540
L1	3.385	3.585	3.785
ØP	3.740	3.840	3.940
Q	2.600	2.740	2.940
R	0.108 REF.		

Revision History

Revision	Release	Remark
V1.0	2023/10/07	Initial Release

Disclaimer

The information given in this document describes the independent performance of the product,but similar performance is not guaranteed under other working conditions,and cannot be guaranteed when installed with other products or equipment.To achieve the required performance of the product in actual scenarios,the customer should conduct a complete application test to assess the functionality of the product.

Allpower assumes no responsibility for equipment failures result from using products at values that exceed the ratings,operating conditions,or other parameters listed in the product specifications.

The product described in this specification is not applicable for aerospace or other applications which requires high reliability.Customers using or selling these products for use in medical,life-saving,or life-sustaining applications do so at their own risk and agree to fully indemnify.

Due to product or technical improvements,the information described or contained herein may be changed without prior notice.