FM8638

SP3T Switch for LTE TRX Application

PRODUCT DESCRIPTION

The FM8638 is a Silicon On Insulator (SOI) Single Pole, Triple Throw (SP3T) antenna switch which require very low insertion loss, high isolation and high linearity performance.

The FM8638 is manufactured in a compact 1.15mm x 1.15mm x 0.45mm, 9-pin surface mount Quad Flat No-Lead (QFN) package.

FEATURES

- Excellent Insertion Loss and Isolation performance
- High Linearity
- GPIO Control Interface
- Broadband frequency range: 0.1 to 3 GHz
- Small package: QFN-9 1.15mm x 1.15mm x 0.45mm
- No DC blocking capacitors required
- 1kV HBM ESD Protection on all pins

APPLICATIONS

- 3G/4G multimode cellular tablets and Multi-Mode GSM, EDGE, WCDMA, LTE
- Diversity antenna switching

Encapsulate information



Absolute Maximum Conditions

Parameters	Symbol	Minimum	Maximum	Units
Supply voltage	V_{DD}	2.5	3.6	V
Control voltage	VCTL		3.0	V
RF input power	Pin		+39.5	dBm
Storage temperature	T_{STG}	-55	+150	℃
Operating temperature	T_{OP}	-40	+90	℃
Human Body Model, Class 1C	ESD	1000		V

试用水印 www.superchip.cn