★ Super Low Gate Charge
★ Green Device Available
★ Excellent CdV/dt effect decline
★ Advanced high cell density Trench technology

Product Summary


BVDSS	RDSON	ID
-20V	6.6mΩ	-60A

Description


The ZX 60P02 is the high cell density trenched P-ch MOSFETs, which provide excellent RDSON and gate charge for most of the synchronous buck converter applications.

The ZX 60P02 meet the RoHS and Green Product requirement with full function reliability approved.

PDFN3x3 Pin Configuration



pin assignment



Schematic diagram

Package Marking and Ordering Information

Product	Package	Marking	Packing	Min Unit Quantity
ZX 60P02	PDFN3*3	*	5000PCS/Reel	5000PCS

Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	-20	V
V_{GS}	Gate-Source Voltage	±12	V
I_D@T_C=25℃	Continuous Drain Current, V_{GS} @ -4.5V[1]	-60	A
I_D@T_C=70℃	Continuous Drain Current, V_{GS} @ -4.5V[1]	-38	A
I_{DM}	Pulsed Drain Current[2]	-220	A
P_D@T_C=25℃	Total Power Dissipation[3]	42	W
T_{STG}	Storage Temperature Range	-55 to 150	℃
T_J	Operating Junction Temperature Range	-55 to 150	℃

Thermal Data

Symbol	Parameter	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction-Ambient [1]	75	℃/W

Electrical Characteristics (T_J=25℃unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D= -250μA	-20	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = -20V, V_{GS} = 0V,	-	-	-1	μA
I_{GSS}	Gate to Body Leakage Current	V_{DS} =0V, V_{GS} = ±12V	-	-	±100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}= V_{GS}, I_D= -250μA	-0.35	-0.65	-1.0	V
$R_{DS(on)}$	Static Drain-Source on-Resistance note3	V_{GS} =-4.5V, I_D =-15A	-	6.6	8.5	mΩ
		V_{GS} =-2.5V, I_D =-12A	-	8	12	
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS} =-10V, V_{GS} =0V, f = 1.0MHz	-	4600	-	pF
C_{oss}	Output Capacitance		-	460	-	pF
C_{rss}	Reverse Transfer Capacitance		-	459	-	pF
Q_g	Total Gate Charge	V_{DS} =-10V, I_D =-15A, V_{GS} =-4.5V	-	56	-	nC
Q_{gs}	Gate-Source Charge		-	8	-	nC
Q_{gd}	Gate-Drain(“Miller”) Charge		-	16	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	V_{DD} =-10V, I_D =-13A, R_{GEN}=2.7Ω,V_{GS} =-10V	-	11	-	ns
t_r	Turn-on Rise Time		-	110	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	157	-	ns
t_f	Turn-off Fall Time		-	160	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current		-	-	-60	A
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	-220	A
V_{SD}	Drain to Source Diode Forward Voltage	V_{GS} = 0V, I_S =-30A	-	-	-1.2	V
trr	Reverse Recovery Time	T_J=25℃,I_{SD}=-15A, V_{GS}=0V di/dt=-100A/μs	-	23	-	ns
Qrr	Reverse Recovery Charge		-	14	-	Nc

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. EAS condition: T_J=25℃,V_{DD}=-10V,V_G=-10V, R_G=5.9Ω, L=0.5mh,I_{AS}=-16A

3. Pulse Test: Pulse Width≤300μs, Duty Cycle≤0.5%

Typical Performance Characteristics

Figure1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Capacitance Characteristics




Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area




Figure 10: Maximum Continuous Drain Current vs. Case Temperature






Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Case




Test Circuit


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



Package Mechanical Data-PDFN3x3-8L



COMMON DIMENSIONS

(UNITS OF MEASURE = MILLIMETER)

SYMBOL	MIN	NOM	MAX
A	0.70	0.80	0.90
b	0.25	0.30	0.39
c	0.14	0.15	0.25
D	3.20	3.30	3.40
D1	3.00	3.15	3.30
D2	2.35	2.45	2.55
e	0.65 BSC		
E	3.25	3.35	3.45
E1	2.85	3.00	3.15
E2	1.635	1.735	1.835
H	0.33	0.48	0.63
K	0.585	0.685	0.785
L	0.30	0.40	0.50
L1	0.05	0.15	0.25
L2	–	–	0.15
Θ	8°	10°	12°